



## SEALING WIRE Data Sheet



The Acme **Sealing Wire** is available in galvanized steel, copper and stainless steel and can be supplied on plastic spools or in cut lengths. The wire consists of a centre core wire and an outer wire, which is spirally lashed around the inner core wire providing an excellent thread type grip to prevent slippage or removal after the seal has been compressed.

### Technical Data

#### Sealing Wire

Wire Reference sizes in (mm)	Fine Lash Galvanised Steel	Medium Lash Galvanised Steel	Fine Lash Copper	Medium Lash Copper	Fine Lash Stainless
<b>0.5kg Reels</b>	WIF 5RL	WIM 5RL	WIFC 5RL	WIMC 5RL	WIFS 5RL
<b>Wire Core Dia.</b>	0.50	0.70	0.50	0.70	0.50
<b>Lash Wire Dia.</b>	0.30	0.45	0.30	0.45	0.30
<b>Total Dia.</b>	1.10	1.60	1.10	1.60	1.10
<b>Length in metres</b>	170	70	170	70	170
<b>Available lengths in packs of 1000</b>	10, 15, 20 30, 40, 45	10, 15, 20 30, 40, 45	10, 15, 20 30, 40, 45	10, 15, 20 30, 40, 45	10, 15, 20 30, 40, 45